

# Dx Series by Shermann

## Bx215



Compact, highly portable LF cabinet with 2 powerful 15" bass drivers.

Standard fittings include pole mount adapter and rear mounted swivel castors c/w additional handles.

Our sturdy TPC coating is the finish used on this model.

Use with SHERMANN Audio Dx cabinets to form a cost-effective, powerful, high quality PA or Disco rig.

## Components

Wiring	2.5mm multi-strand copper
Castors (option)	4 x 100mm swivel type on back
LF drivers	Steel framed 15" / 3" voice coil

### Connections

Speakon NL4	pin 1+ <b>hot</b> / pin 1- <b>cold</b>
Speakon NL8	pin 1+ <b>hot</b> / pin 1- <b>cold</b>

### Crossover/filter frequencies

External:	High pass: -3dB @ 30Hz / 8th order
External:	Low pass: 110 Hz (within SHERMANN Audio systems)

### Specifications

#### System

Format	Ported enclosure
Nom' impedance	4 ohm
Rec' amp' power @ 4ohm	600-1000 watts rms
Programme power	2000 watts

#### Performance

Sensitivity @ 1w/1m	100 dB
Maximum output	130dB @ 1m
Frequency response	40 Hz - 130Hz
Dispersion (>2.5khz)	N/a

#### Components

Drive unit (LF)	380 mm (15") x 2
-----------------	------------------

#### Dimensions

Height	883 mm
Depth	608 mm
Width	577 mm
Depth over castors (option)	736 mm
External volume	298 lts
Weight	62.8 Kgs

#### Mechanical

Connectors	"Speakon" NL4 x 2
(Option)	"Speakon" NL8 x 2
Castors	4 x 100mm swivel
Handles	Insert type
Pole mount (fitted)	35mm
Finish	TRC or TPC
Foam Front / Welded	
Grille	Standard fitting

#### *Please note*

We would like to draw your attention to the likelihood of hearing damage from prolonged exposure to high sound pressure levels.

Care should be taken when using cabinets in close proximity to the audience, musicians or artists.

For further information on the safe operation of any Shermann Audio product please fax, call or email us - contact details are shown below.

The front foam used on this cabinet is not fire retardant.

\* Options must be requested at time of ordering.



## Shermann

Unit 35, Vastre Enterprise Park,  
Newtown, Powys.  
SY16 1DZ

Tel: +44 (0) 1686 622 997  
Fax: +44 (0) 1686 623 233  
Email: [info@shermann.com](mailto:info@shermann.com)  
Web: [www.shermann.com](http://www.shermann.com)